STATEMENT OF COMPLIANCE Clear Slip Resistant Coating

The Australian Building Code requires that all materials used in building construction is to comply with specific criteria to enhance public safety.

This certificate confirms that the product detailed below, installed as per our specifications, complies with the specifications currently published by NCC, AS 4586-2013 Appendix A Slip Resistant Classification of new Pedestrian Surface Materials Wet Pendulum Test Method.

Slip Resistant Rating P3

Product Includes:

Product Number: CSRCP31 x 10L CWM Part 1Product Name: Clear Slip Resistant Coating P3 (Mild)1 x 1L CWM Part 2

Manufacturer/Brand name: Remedial Membranes 1 x Large Bag of Aggregate A

To achieve the tested rating results.

Coating to achieve up to 66m2 coverage and ½ tablespoon or 10ml of 'Aggregate A' per m2 to be used to achieve the slip resistant finish on a smooth surface.

Test Surface: Smooth tile.

If the surface that you are installing the Clear Slip Resistant Coating (CSRC) on is NOT smooth, we suggest that you use the next Aggregate grade on the list to achieve a similar finish. For example, if you are trying to achieve a <u>P4</u> rating but your surface is not smooth, then we would suggest that you use the listed aggregate to achieve a <u>P5</u> rating on your surface.

Residential Applications

The coating has a 5-year expected life span.

Commercial Applications

It is impossible to characterize the expected wear and tear of different commercial applications, so we suggest that all Commercial Applications be inspected yearly by an Accredited Installer of the Clear Slip Resistant Coating.

Note:

The Clear Slip Resistant Coating is classified a permanent application and is not able to be removed.

Contact Details

Remedial Membranes Pty Ltd

ABN: 59 611 253 117 Phone: 02 8012 2716

Postal Address: PO Box 87, Bonville NSW 2450 Website: www.remedialmembranes.com.au